

0.025mm Printing Accuracy Smt Production Line Stencil Printer Machine Automatic

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 set
- Packaging Details: Wooden case
- Delivery Time: 4 weeks after payment

CHINA

ETON

CCC

ET-F400

T/T, Western Union

50 sets per month

- Payment Terms:
- Supply Ability:



Product Specification

- Apply:
- Smt Production Line 6~200 Mm/sec
- 60°/55°/45°
- Squeegee Angle:Packing:

• Squeegee Speed:

- Printing Accuracy:
 - Ste
- Name:Highlight:
- Wooden Case ±0.025mm
- Stencil Printer
- smt pick and place machine, smt pick and place equipment

Our Product Introduction

ET-F400 Automatic stencil printer

SMT production line

In the automatic smt production line, loader machine send board to printer, then through the conveyor, pcb board sent to pick and place machine from printer, after mounting components, pcb board sent to reflow oven, once again bonding the reinforcing element to the pcb board. Lastely, unloader machine would collete the processed pcb board. ET-F400 apply to smt production line, it is automatic, totally printing by machine.

PCB size

ET-F400 max pcb size is 400*340 mm, min size is 50*50 mm, thickness is 0.4-6 mm, pcb warpage no more than one percent.

PCB location

PCB support system is magnetic pin/up-down table adjust/supportblock. Clamping system is side clamping and vacuum nozzle.

Screen frames

ET-F400 max screen frames size is 737*737 mm, mmin size is 370*370 mm, thickness is 25-40 mm.

Transport system

ET-F400 transport height is 860-940 mm, transport direction is left-right, right-left, left-left or right-right. Max transport speed is 1500mm/s programmable.

Print head

ET-F400 have two independent motorised printheads.



Squeegee parameter

Squeegee Speed	6~200mm/sec
Squeegee Pressure	0~15Kg
Squeegee Angle	60°/55°/45°
Squeegee Type	Stainless steel(Standard), plastic
Stencil Separation Speed	0.1~20mm/sec Programmable

Cleaning system

There are three ways to cleaning, dry, wet, vacuum.

Parameter of machine

Repeat Position Accuracy	±0.01mm
Printing Accuracy	±0.025mm
	<7s (Exclude Printing & Cleaning)
Product Changeove	<5Min
Air Required	4.5~6Kg/cm ²
Power Input	AC:220±10%,50/60HZ 1Ф 3KW
Control Method	PC Control
Machine Dimensions	1220(L)X1355(W)X1500(H)mm
Machine Weight	Approx:1000Kg

Our service

We provide one year standard warranty.
 We will sent our engineer to install and traning for freely.
 We will provide The latest technical support

F&Q

1.Is your software interface in English?
English interface and chinese interface are both available.
2.Which counties have your machine exported?
Our machine have expored more than 20 countries, such as India, Egypt, Korea, Turkey, Brazil, Vietnam, and so on.
3.Who is your client?
Such as FSL, ETI, KONKA, OPPLE, MLS are our client. In India, such as RK,Surya, skyquad are our client.

Shenzhen Eton Automation Equipment Co., Ltd.							
C	0086 13670197725 (Whatsapp/Wechat)	0	linda@eton-mounter.com	æ	smtmountingmachine.com		
	HENGFENG INDUSTRIAL AREA,ZHOU STREET,		ROAD NO. 739,HEZHOU COI AN,SHENZHEN,CHINA	MMUN	ITY,HANGCHENG		