



Flexible Strip Magnetic Desktop Pick And Place Machine 200000CPH High Speed

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: ETON
- Model Number: HT-T9
- Minimum Order Quantity: 1 set
- Price: EXW USD 95000/sets
- Packaging Details: Our packing is made of wooden box with vacuum package, and we promise to deliver the goods within four weeks after payment.
- Delivery Time: 30 days after deposit
- Payment Terms: T/T
- Supply Ability: 50 sets per month



Product Specification

- Name: Pick And Place Machine
- Components: LED 3014/3020/3528/5050 Resistor Capacitors
- Feeders: 64 PCS
- Nozzles: 64 PCS
- Speed: 200000CPH
- PCB Size: 250mm*any Length
- Highlight: **high speed led mounting machine, smt assembly machine**

for more products please visit us on smtmountingmachine.com

Product Description

LED light 5m 50m flexible strip magnetic pick and place machine

Features

Producing with 2~4 types of materials with high capacity, available for 5m, 50m or any length of flexible strip and roll to roll. dual-arm four module, 15 nozzles, for each mounting part, part A/B/C/D can be mounted separately or synchronously. Calibration automatically, high precision, available for RGB.

Strong independent research and development capability

Exclusive patent technology: group to pick and group to mount.
Motion control card module 1 set R&D by ETON.
Electrical control R&D by ETON.
Vision for the flight identification, mark correction

Product presentation

High Speed: Applying the exclusive patented technology of group-based and group-based pasting, the pasting speed is 200000 CPH, 64 feeders station and 64 nozzles. It can automatically transmit on-line. And It can produce 2-4 kinds of materials at the same time, which greatly improves the efficiency.
Strong durability: The quality of hardware equipment is guaranteed by certificate, the quality of dual motor electronic flying and guide rail and screw is guaranteed, which can support 24-hour operation.
Simple operation: Windows 7 system can be used to switch the Chinese-English interface, usually 3 to 5 days training of operation is enough.



Technical parameter

HT-T9		
PCB	PCB length width	250mm*any length
	PCB thickness	0.5~1.5mm
	PCB clamping	Adjustable pressure pneumatic
	Mounting mode	Group to take and group to mount
O.S.	system	Windows 7
	software	R&D independently
	display	LED monitor
	Input device	Keyboard, mouse
	No. of camera	5 sets of imported camera Vision alignment, mark correction
	Mounting precision	0.02mm (repeat precision)
	Mounting height	<15mm
	Mounting speed	100000~150000CPH

Vision system	Components	LED 3014/3020/3528/5050 and resistors,capacitors ,bridge rectifiers.
	Components space	0.2mm
	No.of feeders station	64PCS
	No.of nozzles	64PCS
	Power	380AC 50HZ
	Power consumption	6KW
	Conveyor transmission	Belt drive
	Transmission speed	>500mm/sec
	Transmission direction	Single (left to right or right or left)
	Transmission mode	Auto online drive
	Position mode	Optical
	Air pressure	>5.0kg /cm ²
	Electrical control	Independent research and development by ETON
	Motion control card module 1set	Independent research and development by ETON
	X,Y,X axis drive way	Servo motor control for X,Y,Z axis
	Feeding way	Electric feeder with double motor

Remarks:

- 1.Payment terms: Deposit 30% in advance,the balance 70% should be paid before shipment by T/T.
- 2.Delivery time: 30 days after deposit.
- 3.Warranty: 1 year.(including spare parts)



Shenzhen Eton Automation Equipment Co., Ltd.



0086 13670197725 (Whatsapp/Wechat)



linda@eton-mounter.com



smtmountingmachine.com

HENGFENG INDUSTRIAL AREA,ZHOUSHI ROAD NO. 739,HEZHOU COMMUNITY,HANGCHENG STREET,BAOAN,SHENZHEN,CHINA