

# 36mm Height SMT Mounting Machine 80000CPH For Led Flexible Roll

## **Basic Information**

• Place of Origin: CHINA Brand Name: ETON HT-E8D-1200 Model Number: • Minimum Order Quantity: 1 set • Price: FOB USD 81000/sets • Packaging Details: Our packing is made of wooden box with vacuum package, and we promise to deliver the goods within four weeks after payment. • Delivery Time: 30 days after deposit • Payment Terms: T/T Supply Ability: 50 sets per mouth



## **Product Specification**

- Name:
- Dimension:
- Power:
- 3150\*2250\*1650mm 380AC 50HZ

<36mm

8KW

Pick And Place Machine

- Mounting Height:
- Visual Camera:
- Power Consumption:
- Highlight:
- 36mm Height SMT Mounting Machine, SMT Mounting Machine 80000CPH, Led Flexible Roll SMT Mounter

2 Sets Of Imported Camera

#### Full Automatic SMT mounting machine for led flexible light roll and roll

### Details

The Difference between Double Module Mounting Machine and Single Module Mounting Machine is that the double mounting machine have dual system and to produce two different products at same time.

This is a multifunctional pick and place machine, it is can mounting LED,capacitors,resistors,IC,shaped components,etc. This machine can meet the needs of producing two kinds of products at the same time. The mounting speed reaches 80,000 CPH, which greatly improves the production efficiency.

### Applications

Applicability is wide and the pick and place machine can be used in the production of tube light, down light, panel light, bulb, outdoor displays etc.

Most of the electronic components can be mounted on the classification of a variety of led chips, IC components, lens, shaped components, etc.

The minimum of 0402 SMT component specification size, the highest mount is 36 mm , can satisfy the production variety products manufacturers



HT-E8D		
PCB	PCB length width	Max:1200*300mm min:100*100mm
	PCB thickness	0.5~5mm
	PCB clamping	Adjustable pressure pneumatic
	Mounting mode	Group to pick and separate to place
		Separate to pick and separate to place
O.S.	system	Windows 7
	software	R&D independently
	display	Touch screen monitor
	Input device	Keyboard, mouse
Vision system	No.of camera	2sets of imported camera
		Vision for the alignment identification, mark correction
	Mounting precision	0.02mm(repeat precision)
	Mounting height	<36mm
	Mounting speed	80000CPH
	Components space	0.2mm
	Power	380AC 50HZ
	Power consumption	8KW
	Conveyor transmission	Max length:500mm
	Transmission speed	>500mm/sec
	Transmission direction	Both direction
	Transmission mode	Auto online drive
	Air pressure	>5.0kg /cm <sup>2</sup>
	Electrical control	Independent research and development by ETON



We exported machine to more than 20 countries



# Our Services





#### FAQ

#### 1, What's the terms of payment? What about the trade term?

T/T is OK. You can choose FOB Shenzhen.

2, What is the delivery date?

We will deliver the goods after 30 days' deposit.

#### 3, What mode of transport does the goods adopt?

Our mode of transportation is very flexible. Our mode of transportation including water, land and air transportation. You can choose the most suitable way according to your requirements.

4, What is the direction of transmission of machines?

The transmission direction of this machine is single direction. From left to right or from right to left.

5, How about your operating system?

The operating system is Windows 7. The software is developed independently. It supports Chinese and English operation interface. And It has simple structure and is easy to operate.

