

# 4mm Wide 220V Pcb Inspection Conveyor Multi Segment Transmission

# **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 set
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:

# 

# **Product Specification**

- Name:
- PCB Conveyor

900±20mm

(600~2500)\*1050\*900 Mm

80\*50~ (510-1500)\*390 Mm

CHINA

ETON

BC390

T/T

CE,SIRA,CCC,ISO

EXW USD 4000/sets

30 days after deposit

50 sets per mouth

Our packing is made of wooden box with vacuum package, and we promise to deliver the goods within four weeks after payment.

- Dimensions:
- 70~110 Kgs
- Net Weight:PCB Size:
- Transport Height:
- Transport Direction:
- Highlight:
- Left-Right; Right-Left; 220V Pcb Inspection Conveyor, 4mm Pcb Inspection Conveyor, 4mm Wide smt conveyor



**Our Product Introduction** 

### 4mm Wide 220V Pcb Inspection Conveyor Multi Segment Transmission

### 220V PCB conveyor Smt Machine in SMT production line

### Product Features of PCB conveyor

The movable working table, Visible Board document and lighting rack are arranged on the basis of the conveyor; The lighting brightness, operation height and other user-friendly design, the operation is more efficient, convenient and practical; Green flat imported anti-static transmission belt, durable, easy to replace; Sheet metal weighted structure, overall stable, not easy to shift; PLC control system through SMEMA communication.

### Product optional features of PCB conveyor

Two-segment transmission or multi-segment transmission (the minimum length of each segment is 0.5 meters); Two sections of independent adjustment width mode;

Install cooling fan, blocking cylinder, shelving table, dust cover and other additional configurations;

Special program requirements such as checking function with scanner and NG/OK communication function with AOI.

### Specification of pcb conveyor

Description	This equipment is used to transfer the circuit board in the production line
Transport height	900±20mm
Transport direction	Left-Right; Right-Left; (Can switch with one key)
Power Consumption	Single-phase AC110 220V (optional), up to 50 volt amperes
Transport speed	0.5~20 meters per minute (or customer specified)
Conveyor belt type	4mm wide flat belt
Model	BC390
PCB Size(L*W)(mm)	80*50~ (510-1500)*390
Dimension(L*W*H)(mm)	(600~2500)*1050*900/(The height of the lamp holder 1800)
Approximate weight (Kg)	About 70~110





### Logistics and delivery

Our mode of transportation including water, land and air transportation. You can choose the most suitable way according to your requirements. Our packing is made of wooden box with vacuum package, and we promise to deliver the goods within four weeks after payment.

### Packaging & Delivery

Our mode of transportation including water, land and air transportation. You can choose the most suitable way according to your requirements. Our packing is made of wooden box with vacuum package, and we promise to deliver the goods within four weeks after payment.

### FAQ

### 1. Choose which mode of transportation?

Our modes of transportation are flexible, including water, land and air transportation.

2. Do you have oversea after sale service?

We can offer technical support abroad. If you have any technical problem, our engineers will support you promptly.

3. What is the delivery date?

We will deliver the goods after 30 days' deposit.

4. Is this machine easy to operate?

Of course, the operating system supports Chinese-English interface display, easy to understand and operate.

### 5. Why choose us?

Leading SMT Supplier in China; In the LED industry market share is in an absolute leading position.

