

# 180000CPH pick and place arm SMT mini pick and place machine for SMT line

### **Basic Information**

. Place of Origin: **CHINA** Brand Name: **ETON** 

· Certification: CE,CCC,SIRA Model Number: HT-F7S • Minimum Order Quantity: 1 set

• Price: EXW USD 45000-67500/sets


 Packaging Details: Our packing is made of wooden box with

> vacuum package, and we promise to deliver the goods within four weeks after payment.

. Delivery Time: 30 days after deposit

• Payment Terms:

. Supply Ability: 50 sets per mouth



# **Product Specification**

Name: Chip Mounter Machine

68 PCS • Feeders:

Components: LED 3014/3020/3528/5050 Resistor

Capacitors

Nozzles: 34 PCS

150000~180000CPH Speed:

. Mounting Height:

. Applicable Components:

• PCB Size: 250mm\*any Length 1200\*330mm Pcb Size: 0402--5050,etc


SMT Machine Related Products Type:

±0.02mm • Repeat Accuracy: 1 Year Warranty:



## More Images





### **Product Description**

## 180000CPH pick and place arm SMT mini pick and place machine for SMT line

#### Features of SMT pick and place machine

Exclusive patent technology: Group to pick and group to mount.

High speed:150000~180000 CPH,with 34 heads

Two mounting modules, 18 nozzles for each mounting part, part A and part B can be mounted separately or synchronously.

Apply to the 0.6 M, 0.9 M, 1.2 M rigid PCB and 0.5 M, 1 M LED flexible strip. Producing with 2~4 types of materials with high capacity. available f or board with any proportion of LED chip and resistor.

#### Technical parameter of SMT pick and place machine

PCB Length Width	Max:1200*330mm Min:100*100mm
No. of Camera	5 sets ( Digital camera)
	Vision alignment, MARK correction
	±0.02mm(Repeat precision)
Mounting Height	≦5mm
Mounting Speed	150000~180000 CPH
Components	LED 3014/3020/3528/5050 and capacitors, resistors, bridge rectifiers, etc.
Components Space	0.5mm
Power	380AC 50 HZ
Power Consumption	6kw
Operating Environment	23 ±3



With high assembly density, small size and light weight of electronic products, the volume and weight of SMD components are only about one-tenth of traditional plug-in components. Generally, after SMT is adopted, the volume of electronic products is reduced by 40%~60%, and the weight is reduced by 60%~ 80%.


High reliability and strong anti-vibration ability. The defect rate of solder joints is low.

Good high frequency characteristics, reducing electromagnetic and radio frequency interference.

It is easy to realize automation and improve production efficiency. Reduce costs by 30%~50%. Save materials, energy, equipment, manpower, time, etc.



#### **Compony Views**





Shenzhen Eton Automation Equipment Co., Ltd.





