Smt mounting machine for soft flexible strip roll to roll

Basic Information

- Place of Origin: CHINA
- Brand Name: ETON
- Certification: CCC,SIRA,CE
- Model Number: HT-T9
- Minimum Order Quantity: 1PCS
- Packaging Details: WE USE VACUUM WOODEN BOC PACKAGE
- Delivery Time: 5-8 work days
- Payment Terms: L/C, T/T
- Supply Ability: 50PCS/Month

HT-T9

Product Specification

- Warranty: 1 Year
- Name: SMD Chip Mounter,SMT Pick And Place Machine,SMT Chip Mounter
- Application: SMD Production Line,SMT Production Line,for SMT Machine
- Power Supply: 380V 50HZ
- Condition: New,100% Original,Brand-new
- Product Name: Place Machine\ LED Mounter\LED Assembly Machine,Automatic SMT Mounting Shooter
- Weight: 1700KG
- Mounting Speed: 250000 CPH
- Usage: Circuit Board Assembly,SMT Mounting Machine,SMD,LED
- Dimension: 3100*2300*1550mm
- Feeders: 68PCS
- Pcb Thickness: 0.5-1.5MM

HT-T9

More Images

HT-T9
Components:LED 3014/ 3020/ 3528/ 5050 and capacitors, resistors, bridge rectifiers, etc.

Product Description

Smt mounting machine for soft flexible strip ROLL TO ROLL

Quality Identification
1.flexible LED lamp band is the use of FPC do assembly circuit board, with chip LED assembly, so that the product thickness is only a coin thickness, does not occupy space; And can be cut at will, but also can be arbitrarily extended without affecting the luminescence. FPC is made of soft material, which can be bent, folded and wound at will. It can be moved and 3D at will without breaking. Suitable for irregular places and narrow space, but also because it can be arbitrary bending and winding, suitable for any combination of various patterns in advertising decoration.
2.LED hard strip is made of PCB hardboard assembly circuit board, LED useful chip LED assembly, also used straight-in LED assembly, depending on the needs of different components. The advantage of hard strip is easier to fix, processing and installation are more convenient; the disadvantage is not free to bend, not suitable for irregular places.

Parameter
Dimension:3100*2300*1550mm
Total Weight:1700 kg
PCB Length Width:250*any length
PCB Thickness:0.5-1.5mm
PCB Clamping:Vacuum adsorption, cylinder splint, adjustable track width
Mounting Mode:Group picking and separately placing
Mounting speed: 200000~250000 CPH
Repeat mounting Precision:±0.02mm (Repeat precision)
Mounting Height:≦5mm
Components:LED 3014/ 3020/ 3528/ 5050 and capacitors, resistors, bridge rectifiers, etc.

FAQ
Q:can you help me find raw material suppliers?
A:OK,I will try my best to find for you,will let you know as soon as I find it,friend.
Q:can you suggest a suitable machine for LED light?
A:we have many types of machines that can be produced,can you share pictures of your products?
Q:I want to discuss with you about the assembly machine
A:I would advise you not yo buy assembly line yet because assembly line are very expensive,it can be assembled manually first.