

## 380V 50HZ SMD Chip Mounter Automatic SMT Pick And Place **Machine**

#### **Basic Information**

. Place of Origin: **CHINA** Brand Name: **ETON** 

· Certification: CCC,SIRA,CE Model Number: HT-E8D-1200

• Minimum Order Quantity: 1PCS

WE USE VACUUM WOODEN BOC Packaging Details:

**PACKAGE** 

. Delivery Time: 5-8 work days Payment Terms: L/C, T/T Supply Ability: 50PCS/Month



### **Product Specification**

Model: HT-E8D-1200 Warranty: 1 Year, 12 Months

Name: SMD Chip Mounter, SMT Pick And Place

Machine, SMT Chip Mounter, smt Nozzle

SMT Mounting Shooter Machine, SMT · Application:

Production Line, for SMT Machine

. Power Supply: 380V 50HZ

• Condition: New,100% Original, Brand-new

Product Name: Place Machine\ LED Mounter\LED Assembly

Machine, Automatic SMT Mounting

Shooter, SMT Shooter Machine

. Weight: 2500KG . Mounting Speed: 90000 CPH Type: Automatic

Usage: Circuit Board Assembly, SMT Mounting

Machine, SMD, LED

01E0\*00E0\*16E0~~



#### **Product Description**

#### SMD chip mounter for SMT pick and place machine

HT-E8D is a dual system, dual module multifunctional mounter to produce two different products at the same time, it can mount the component range from 0402 to 15mm.and e8d has two guide rail, and each rail can produce a product, and the one side is wrong the other side will continue E8D-1200 is suitable for the largest PCB board size of 1200 \* 300mm.mini size 100\*100mm.with a production capacity of 90000 CPH. for the E8 series model,we can provide customized service ,according to your size of your PCB size make the proper machine for your products. in order to service our customers better.

#### **Technical parameter**

Model:E8D-1200

Dimension:3150\*2250\*1650mm

Total Weight:2500kg

PCB Length Width:Max:1200\*300mm Min:100\*100mm

PCB Thickness:0.5-5mm

PCB Clamping:Adjustable pressure pneumatic

Mounting Mode:Group picking and separate placingseparate picking and separate placing

No. of Camera:4pcs

Mounting Precision:±0.04mm

Mounting Height:<15mm (Automatic Changing)

Mounting Speed:90000 CPH

Components:LED, capacitors, resistors, IC, shaped components, etc.

Components Space:0.2mm

No. of Feeders Station:48pcs

No. of nozzles:24pcs Power:380AC 50HZ Power Consumption:8 KW

Conveyor transmission:Max length :1200 mm

Transmission Speed: 1000mm/sec



#### LED driver applications



LED driver applications in the lighting industry at present our LED power supply is also the core component of LED lights, in good market expectations, a large number of manufacturers into the LED drive power supply directly by the decision of the life of LED lamps and lanterns. However, the driving power depends on the quality of LED lamps and lanterns an important part of the power supply can directly affect the quality of LED lighting. Especially for outdoor lighting, its power supply must have strict waterproof function, otherwise it can not withstand the poor use of the environment. The common LED lamp power supply driving shape currently LED has been widely used, including LED tubes, bulbs, lamp belts, street lamps and other audience is the most widespread. Different LED lights use different power drivers.

# Shenzhen Eton Automation Equipment Co., Ltd.

**O** 0086 13670197725 (Whatsapp/Wechat)

linda@eton-mounter.com

e smtmountingmachine.com

HENGFENG INDUSTRIAL AREA, ZHOUSHI ROAD NO. 739, HEZHOU COMMUNITY, HANGCHENG STREET, BAOAN, SHENZHEN, CHINA