



## Automatic printer vision alignment system for LED FPCB board printing

### Our Product Introduction

for more products please visit us on [smtmountingmachine.com](http://smtmountingmachine.com)

#### Basic Information

- Place of Origin: China
- Brand Name: ETON
- Certification: CE,CCC,SIRA
- Model Number: ET-AL1025L
- Minimum Order Quantity: 1 set
- Packaging Details: Packing in film package and foam cotton, and covering vacuum bag within sturdy wooden boxes.
- Delivery Time: 30 days
- Payment Terms: T/T
- Supply Ability: 50 sets per month



#### Product Specification

- FPCB Min Size: 50MM
- FPCB Max Size: 260MM
- FPCB Thickness: 0.5-5MM
- FPCB Warpage: Max. FPCB Diagonal 1
- Transport Direction: Left-Right
- Transport Height: 900±40mm
- Squeegee Speed: 6~300mm/sec
- Squeegee Type: Stainless Steel(Standard), Plastic



## Product Description

### Automatic printer vision alignment system for LED FPCB board printing

#### Machine configuration

- Programmable suspension printing head;
- \*Two sets of stepping motor drive, the pressure of front and rear scraper can be adjusted separately to ensure the inconsistency of front and rear printing caused by fatigue deformation of scraper material;
- \*Effectively control the stroke, improve the printing efficiency, and prevent the leakage of solder paste;
- Standard stainless steel scraper, unique design, improve the service life of the blade;
- Downward vision alignment system;
- CNC guide rail adjustment;
- Industrial controlled computer, Windows XP interface operating system;
- Built-in software diagnostic system;
- SMEA interface.

#### Technical parameter

Screen Frames	Min Size	850mm
	Max Size	550mm
	Thickness	25~45mm
FPCB Min Size		50mm
FPCB Max Size		260mm
FPCB Thickness		0.5~5mm
FPCB Warpage		Max. FPCB diagonal 1
Transport Height		900±40mm
Transport Direction		Left-Right
Transport Speed		Max 1000mm/S Programmable (Adjustable)
Board Location	Support System	Platform jacking tension
	Clamping System	Edge clamp fixed
Print head		Two independent motorized print heads
Squeegee Speed		6~300mm/sec
Squeegee Pressure		0~10Kg/cm <sup>2</sup>
Squeegee Angle		55°(Standard)
Squeegee Type		Stainless steel(Standard), plastic
Stencil Separation Speed		0.1~20mm/sec Programmable
Cleaning System		Manual cleaning
Table Adjustment ranges		X:±5mm;Y:±5mm;θ:±2°
Machine		
Repeat Position Accuracy		±0.01mm
Printing Accuracy		±0.025mm
Cycle Time		≤9s (Exclude Printing & Cleaning)
Air Required		4.5~6Kg/cm <sup>2</sup>
Power Input		AC:220±10%,50/60HZ 1Φ 1.5KW
Control Method		PC Control
Machine Dimensions		1754(L)X1249(W)X1600(H)mm
Machine Weight		Approx:600Kg
FPCB transport over plate height		20mm

#### Our Exhibitions

Eton has participated in many exhibitions of foreign countries, such as India Mumbai Exhibition, India Delhi Exhibition, Egypt Exhibition, Turkey Exhibition, Pakistan Exhibition, etc and trading with more than 30 countries. Furthermore, we have took part in our domestic large exhibition, like Guangzhou Guangya Exhibition, Shanghai Munich Exhibition, Chongqing LED light Exhibition, etc.



## Service

Pre-sale service

Provide suitable production plan

Advise on plant electrical equipment and layout

Sale service

Report machine status in time

Follow up and send test machine video

After-sales service

Software lifetime upgrade

24 hours to deal with problems online

Engineers can arrive on site to teach operation and debug the machine

Regular visit (one year warranty period, spare parts repair free; Once or twice a year after warranty)



## Shipping and Delivery

Shipping Way:

By air, for sample and small package

By sea, for large package and quantity;

Other ways as customer requested.

Delivery Time:

Within 30 Days.

## Professional and standard packaging



**Step one: Pack the machine with foam cotton and stretch film to protect the outside of the machine**



**Step two: Vacuum packaging**  
put the desiccant in a vacuum bag to prevent moisture; use straps to secure the machine;



**step three: professional wooden box packaging**

## FAQ

Q. What is your actual speed of your products?

A. For the actual speed of the machine which is constrained by many factors, that related to the number of the components, the time to send PCB board and receive the board, etc. And is decide for the actual products and needs.

Q. How many components can your pick and place machine mount in a PCB board?

A. While this is for our clients needs and the size of the PCB board.

Q. How many products can your machine make per day?

A. The capacity of our machine is according to the real products, and the number of components on your PCB board that is important factor to figure out the actual speed of our machine with your products.

**Contact me:**

**Whatsapp/Wechat: +8613632769526**

**Email: Noah@eton-mounter.com**



**Shenzhen Eton Automation Equipment Co., Ltd.**



0086 13670197725 (Whatsapp/Wechat)



[linda@eton-mounter.com](mailto:linda@eton-mounter.com)



[smtmountingmachine.com](http://smtmountingmachine.com)

HENGFENG INDUSTRIAL AREA,ZHOUSHI ROAD NO. 739,HEZHOU COMMUNITY,HANGCHENG  
STREET,BAOAN,SHENZHEN,CHINA