

Docking Cart Electrical Board SMT Mounter Machine 2 Modeuls 20 Mounting Heads

Basic Information

Place of Origin: ChinaBrand Name: ETON

Certification: CCC/CE/SIRA

Model Number: YT202S



Product Specification

Machine Name: SMT Machine / Pick And Place Machine/

Mounte

• Machine Heads: 2 Modeuls, Total 20 Mounting Heads

Machine Speed: 80000 CphMachine Application: PCBA

• Highlight: 20 Heads SMT mounter machine,

cart electrical board SMT mounter machine , $% \label{eq:cart} % \begin{subarray}{ll} \end{subarray} % \beg$

2 Modeuls SMT Mounting Machine

Product Description

YT202S Docking cart electrical board mounter machine

Features

High-speed and intelligent, ultra performance
Using high-speed multi modular head
Non replace modular head
Apply to 0201-40*40mm tape reel package and IC tray feeder
The optimum speed could be reach 80000 CPH

Machine Highlights

Adopt High-speed Multi Modular Head, apply to ultra small chip 0201-40*40mm large chip, wider component range. Brand new flight vision camera, improve recognition performance, size up to 40*40 mm, apply to BGA or CSP etc. Each placement head with independent detection function, which improves the stability of the equipment and the reliability of the product

Mark recognition: High-precision Mark recognition system, adopt 3-color illumination recognition, apply to any shape Mark and LENS(Blue-ray scan), wider range of applications.

Fixed flight vision camera: High-speed flight vision camera, quickly captures multiple head images at once, perform visual calibration of image position, alignment correction, adjustable light source brightness.

Double side docking cart slot 32 PCS, tape reel packages: 64 PCS(Single side docking cart slot 16 PCS, tape reel packages:32PCS), freely switching between docking cart and IC tray feeder (IC tray feeder: Option)

Support YT series double head intelligent electric tape reel feeder, by optically correcting the feeding position of the component, it can achieve stable, accurate and high-speed feeding.

Support multi-layer tray feeder(IC tray feeder) installment, freely switching between docking cart and IC tray feeder. Combine high accuracy Mark recognition camera with fixed flight vision camera, ensure placement accuracy, Software AI intelligent learning function and automatic optimization function.

Machine parameters

Outline dimension

Length	2788 mm	
Width	1686 mm	
Height	1375 mm	
Total weight	1700 kg	

PCB dimension

1 es amendion		
	Max size	
PCB size(L*W)	500*450 mm(single pcb)	
	500*300 mm(double pcb)	
PCB thickness	0.5-4.5 mm	
PCB clamping	Cylinder clamping, track width adjustable	
Rail	2 Rails, 2 gantries	

Mounting head dimension

No. of Mounting heads	20 PCS
Mounting height	≦20 MM
Mounting speed	80000 CPH (Optimum speed)
Feeding way	Intelligent Double Head Feeder



YT202S Mounter 20 Heads, 80000CPH Application: PCBA(Different Size)

Service

Support engineer visit, free install and training on site!



O 0086 13670197725 (Whatsapp/Wechat)

linda@eton-mounter.com

smtmountingmachine.com

HENGFENG INDUSTRIAL AREA,ZHOUSHI ROAD NO. 739,HEZHOU COMMUNITY,HANGCHENG STREET,BAOAN,SHENZHEN,CHINA