

SMT FULL AUTOMATIC SINGLE RAIL LOADER MACHINE

Basic Information

- Place of Origin:
- Brand Name: ETON
- Certification:
- Model Number:
- Minimum Order Quantity: 1PCS
- Packaging Details: WE USE VACUUM WOODEN BOC
 PACKAGE

CHINA

ET-L390

CCC,SIRA,CE

5-8 work days

L/C, T/T

- Delivery Time:
- Payment Terms:

Product Specification



- Warranty:Name:
- Application:
- Power Supply:
- Condition:
- Transmission Height:
- Dimension:
- MODEL:

LOADER MACHINE

- SMD Production Line,SMT Production Line,for SMT Machine
- 220V 50HZ
- New,100% Original,Brand-new
- H=920±30
- 1500*920*1200±30mm
- ET-L390





Our Product Introduction

SMT FULL AUTOMATIC LOADER

SPECIFICATION

Item:ET-L390 send board machine Dimension:L1500*W920*H1200±30mm Frame:Special aluminum profile guide rail and special thousand bird type plastic chain Lift:120W Taiwan brake motor drive uses ball screw to make Magazine stepping up and down Transmission motor:Taiwan 15W fixed speed motor Structure:Pneumatic clamp structure Turnover box specifications:(L)535*(W)460*(H)565mm Maximum size of PCB:(L)530*(W)390mm Lift platform pitch selection:Lift platform pitch selection Transmission height:H=920±30 Operation control panel:Display control true color touch screen power supply:220V 50HZ No. of Full load storage board:50 PCS Gas source:0.4-0.6MPa Electric control box:1set



Other names

Loader machine, also known as falling machine, stacking machine, stacking machine, lift plate machine, palletizing machine.

Features

The advantage of the automatic plate-loading machine is that it does not need the special equipment foundation, can be placed on the hardened flat ground and can be used with the plate-feeding machine, which reduces the labor intensity of the operating workers, improves the working efficiency and saves labor, the whole equipment has the characteristics of simple and reasonable structure, flexible operation, reliable performance and wide range of application.

Installation notes

1. First of all, determine the direction of the plate, generally when the brick machine, mixer a line installed with side plate; brick machine, mixer placed vertically using the back plate.

2. Make sure that the oil cylinder or other moving mechanism is not above the pallet, which will affect the lower pallet. If there is any influence, move the pallet and feed pallet away.

3.Confirm the partner of non-fired brick machine-the square tube that fixed sprocket position in front of the upper plate machine does not touch the belt machine; 4.Under the possible circumstances, as far as possible on the plate next to the left position, convenient pallet placement, easy to use.

Industry analysis

1. This machine only need to use forklift, hydraulic transfer truck will stack together 20-30 plate on the plate machine frame, then the machine can automatically complete into the plate, lift, plate delivery and other complete processes, fully automatic operation, save trouble and labor;

2. Non-fired brick machine partner-fully automatic trigger can be completely without special operation, in the case of rising labor costs, for the plant to save 1-2 staff costs, therefore, it has higher economic benefits.

3.Upper Plate machine installation is simple, in the machine side board, can also be in the rear board. Do not have to do a separate foundation, do not need to under the embedded parts, in the existing cement level can be installed half a day.

Cetificate

for more products please visit us on smtmountingmachine.com



We worked with many brands, and received a lot good reputations because of our excellent services and good quality products

We cherish each opportunity to service for all our customers, aimed to a long term cooperation .

