

For various shape products LED lens 90000 CPH SMT glue dispenser

Basic Information

- Place of Origin:
- Brand Name: ETON
- Certification:
- Model Number:

• Payment Terms:

- Minimum Order Quantity: 1 set
- Packaging Details: Packing in film package and foam cotton, and covering vacuum bag within sturdy wooden boxes.
 Delivery Time: 30 days

50 sets per month

T/T

China

CE,CCC,SIRA

HT-D12-1200

Supply Ability:



Product Specification

- Warranty:
- Power Supply:

Product Name:

- Condition:
- 380AC 50HZ New

1 Year

- Glue Dispenser HT-D12-1200
- Weight:
- Mounting Speed:
- Dimension:
- PCB Size:

800kg
90000 CPH

- Length: 1800 Mm Width: 1050 Mm Height: 1550 Mm
- 1200*500 Mm



For various shape products LED lens 90000 CPH SMT glue dispenser

D12-1200 features

English interface option, easy to operate;

CCD positioning system, visual positioning compensation automatically, correct the deviation of PCB; Large size track, suitable for different size of PCB;

Contactless high speed injection dispensing head, dispensing glue continuously with high efficiency; Intelligent dispensing head ensure good performance, high efficiency and lower wasting;

Full time of glue volume, auto-prompting lower glue volume;

Dispensing head constant temperature function, ensure the glue in liquid;

Control the dispensing value in milliseconds, ensure the conformity of glue volume;

Online visual programming, more convenient;

Automatic program standby, start up production rapidly, Intelligent manufacturing;

Apply to various kind(round, linear, lattice, etc.) of products;

High performance linear motor drive for X, Y axies, ensure high accuracy in high speed;

Universal signal connecting, connect equipment online easily;

large capacity SSD industrial control system, high speed access ensures system response speed.

Machine main parameter

Model	HT-D12-1200	
Dimension	Length: 1800 mm Width: 1050 mm Height: 1550 mm	
Total weight	800 KG	
Max PCB size	1200*500 mm	
Dispensing accuracy	0.1 mm	
Dispensing speed	90000 CPH	
Dispensing height	<15 mm	
Max running speed	1200 mm/sec	

Packages

Step 1: Packing in film package to prevent dust and water to the machine Step 2: Packing in foam cotton to protect the outside of the machine

Step 3: Packing in vacuum package to keep dry of the machine during transportation

Step 4: Transportation by truck to specified port



Step 1: Film packing and foam cotton prevent the dust and water to preotect the machine;

Step 2: Vacuum package and moisture proof bag, to keep dry of the machine during transportation;

Step 3: Equip with sturdy wooden box and transported by trucks to the specific port.

Service

Maintenance period 1 year

One year warranty during warranty any parts that need to be repaired and replaced will be free.

Software and hardware lifetime maintenance

Free upgrade software, the software is Reach and developed by ETON, so we support whole lifetime free upgrade updates.

Visit customers regularly and gather information

Visit clients regularly. We attend the different exhibitions in different cities every year, at the same time, we will visit local clients and support our service and collect feedback on customer suggestions in time.



Shipping and Delivery

As to the part of shipping and delivery, there are three ways for your reference, and different way is for different situations: Land transportation: suitable for inland countries and it is affordable;

Air freight: for urgent good, and it is the most expensive transportation way;

Shipping: It's suitable for heavy goods, and the convenience and lower cost of shipping which is easy for clients to accept the arrival time of the goods.



HENGFENG INDUSTRIAL AREA, ZHOUSHI ROAD NO. 739, HEZHOU COMMUNITY, HANGCHENG STREET, BAOAN, SHENZHEN, CHINA