

Neon soft strip mounting making machine 2835 5050 chip mounting modol can produce 1000 meter a hour

Basic Information

Place of Origin: CHINABrand Name: ETON

• Certification: CCC,SIRA,CE

Model Number: HT-T9 Minimum Order Quantity: 1PCS

Packaging Details: We use vacuum wooden box packaging

Delivery Time: 5-8days
Payment Terms: L/C, T/T
Supply Ability: 50pcs/month



Product Specification

Brand: ETON
 Model: HT-T9
 Length: 3100mm
 Width: 2300mm
 Height: 1550mm
 Total Weight: 1700kg



More Images





Product Description

Neon soft strip mounting making machine 2835 5050 chip mounting modol

LED soft light belt production machine

many of our machines can produce soft light belts, such as T9, T9 can produce soft light belts of any length of 50 meters, 100 meters, and 200 meters. T9 has 68 Feida and 68 suction nozzles, with a capacity of 250K. At the same time, it produces four different materials without affecting the high production capacity. There are four modules of double film heads and 17 suction nozzles in each group. It has a correction function and can be mounted with RGB.

Equipment required for making soft light strip

PCB Loader--Semi-automatic stencil printer--1.6m Buffer stage--pick and place machine--T9--3m Belf line--6m Belt line--6m Belt line--6m Belt line--7m Belt l

Technical parameter

Technical parameter	
Model	HT-T9
Dimension	
Length	3100mm
Width	2300mm
Height	1550mm
Total Weight	1700kg
PCB	
PCB Length Width	250mm*any length
PCB Thickness	0.5-1.5mm
PCB Clamping	Vacuum adsorption, cylinder splint, adjustable track width
Mounting Mode	Group picking and separately placing
O.S.	
System	Windows7
Software	R&D independently
Display	Touch screen monitor
Input Device	Keyboard, Mouse
Vision System	
No. of Camera	5 PCS (Digital camera)
	Vision alignment, MARK correction
Repeat mounting Precision	±0.02mm (Repeat precision)
Mounting Height	≦5mm
Mounting Speed	200000~250000CPH
Components	LED 3014/3020/3528/5050 and capacitors, resistors, bridge rectifiers, etc.
Components Space	0.5mm
No. of Feeders Station	68 PCS
No. of head	68 PCS
Power	380AC 50 HZ
Power Consumption	6kw
Operating Environment	23 ±3
Conveyor transmission	Max Length :1000 mm
Transmission speed	>500mm/sec
Transmission Direction	Single(left→ right or right→ left)
Transmission Mode	Online drive
Positioning Way	Optical
Gas consumption	0.4-0.6mpa (4-6kgf/cm2)150N/min
Electrical control	Independent research and development by ETON
Motion control card module 1 set	Independent research and development by ETON
X,Y,Z Axis Drive way	High-end magnetic linear motor+ servo motor
Feeding way	Electric feeder with double motor



Packing

Our mode of transportation including water, land and air transportation. You can choose the most suitable way according to your requirements.

Our packing is made of wooden box with vacuum package, and we promise to deliver the goods within four weeks after payment.



- Q: How is the training?
- A: After purchasing our products, you can send your engineers to study in our factory, or we can send our engineers to yourfactory to train your staff for you .
- Q: Do you have a product certification certificate?
- A: Our products have CCC, CE, SRIA certification.
- Q: How about the after-sale service? How about the warranty?
- A: We have a team of professional engineers to solve your problems. Any parts that require repair and replacement are free ofcharge during the warranty period. We can also provide you with training and on-site installation, and support remote control of the machine, the machine uses Chinese and English interface, very easy to operate.



Shenzhen Eton Automation Equipment Co., Ltd.



0086 13670197725 (Whatsapp/Wechat)



linda@eton-mounter.com



smtmountingmachine.com