

LED strip printing 100m SMT production automatic printer machine

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 set
- Packaging Details: Packing in film package and foam cotton, and covering vacuum bag within sturdy wooden boxes.

50 sets per month

CE,CCC,SIRA,ISO

ET-AL1025L

China

ETON

- Delivery Time: 30 working days • Payment Terms: T/T
- Supply Ability:



Product Specification

- FPCB Max Size: • Transport Speed:
- Apply:
- MAX 1200mm/s Programmable

260mm

- Cleaning System:
- Printing Accuracy:
- Power Input:
- Dimension:
- Warranty:
- SMT Production Line Manual Cleaning ±0.025mm AC:220±10%,50/60HZ 1Φ 1.5KW 1754(L)X1249(W)X1600(H)mm
- 1 Year



More Images



Our Product Introduction

LED strip printing 100m SMT production automatic printer machine

Description

Machine configuration

• Programmable suspension printing head;

*Two sets of stepping motor drive, the pressure of front and rear scraper can be adjusted separately to ensure the inconsistency of front and rear printing caused by fatigue deformation of scraper material;

*Effectively control the stroke, improve the printing efficiency, and prevent the leakage of solder paste;

- Standard stainless steel scraper, unique design, improve the service life of the blade;
- Downward vision alignment system;
- CNC guide rail adjustment;
- Industrial controlled computer, Windows XP interface operating system;
- Built-in software diagnostic system;
- SMEMA interface.

Technical parameter


Screen Frames	Min Size	850mm
	Max Size	550mm
	Thickness	25~45mm
FPCB Min Size		50mm
FPCB Max Size		260mm
FPCB Thickness		0.5~5mm
FPCB Warpage		Max. FPCB diagonal 1
Transport Height		900±40mm
Transport Direction		Left-Right
Transport Speed		Max 1000mm/S Programmable (Adjustable)
Board	Support System	Platform jacking tension
Location	Clamping System	Edge clamp fixed
Print head		Two independent motorized print heads
Squeegee Speed		6~300mm/sec
Squeegee Pressure		0~10Kg/cm2
Squeegee Angle		55°(Standard)
Squeegee Type		Stainless steel(Standard), plastic
Stencil Separation Speed		0.1~20mm/sec Programmable
Cleaning System		Manual cleaning
Table Adjustment ranges		X:±5mm;Y:±5mm;θ:±2°
Machine		
Repeat Position Accuracy		±0.01mm
Printing Accuracy		±0.025mm
Cycle Time		≤9s (Exclude Printing & Cleaning)
Air Required		4.5~6Kg/cm2
Power Input		AC:220±10%,50/60HZ 1Φ 1.5KW
Control Method		PC Control
Machine Dimensions		1754(L)X1249(W)X1600(H)mm
Machine Weight		Approx:600Kg
FPCB transport over plate height		20mm

ETON

ETON Automatic stencil printer ET-AL1025



Certificates




Shipping and Delivery

Land transportation: suitable for inland countries and it is affordable;

Air freight: for urgent good, and it is the most expensive transportation way;

Shipping: It's suitable for heavy goods, and the convenience and lower cost of shipping which is easy for clients to accept the arrival time of the goods.



 Inda@eton-mounter.com

 Inda@eton-mounter.com

@ smtmountingmachine.com

HENGFENG INDUSTRIAL AREA, ZHOUSHI ROAD NO. 739, HEZHOU COMMUNITY, HANGCHENG STREET, BAOAN, SHENZHEN, CHINA