

104 Feeders smd mounting machine, 98000CPH SMT Mounting Machine YT20S

Basic Information

Place of Origin: china Brand Name: ETON

• Certification: CE,CCC,SIRA,ISO

Model Number: YT20 Minimum Order Quantity: 1set

Packaging Details: woodencaseDelivery Time: 20 workday

• Payment Terms: T/T

• Supply Ability: 50 set per month



Product Specification

Highlight: YT20S SMT Mounting Machine,
 98000CPH SMT Mounting Machine,

104 Feeders smd mounting machine

D212223

More Images





Product Description

Machine main features

Integrated Placement Head

Lightweight, head is integrally formed, the 10 sets of Z axes are independently controlled by modular magnetic linear motor, which greatly improves the speed, accuracy and stability

Precision Corner System

The modular corner system independently controls the angle of each component to ensure high-precision placement. 10 suction nozzles per head, with a center distance of 16mm.

Vacuum Sensing Device

Each placement head with independent detection function, which improves the stability of the equipment and the reliability of the product.

Ultra-high-speed Capability

Adopting high-end magnetic linear motors and a multi-function Modular head, the placement capability has increased by 25% compared to traditional machines, with an optimum speed reaching 98000CPH

Machine main parameter	
Model	YT20S
Dimension	
Length	1480mm
Width	2680mm
Height	1650mm
Total Weight	2380kg
PCB	T
PCB Length Width	Max:500*300mm(1200*450 option) Min:50*50mm
PCB Thickness	0.5-5mm
PCB Clamping	Cylinder clamping, track width adjustable
Mounting Mode	Group picking and separate placingseparate picking and separate placing
O.S.	
System	Windows7
Software	R&D independently
Display	LED monitor
Input Device	Keyboard, Mouse
Vision System	
No. of Camera	1 PCS (Head flight vision camera)
	2 PCS Mark camera
Mounting Precision	CHIP±0.03mm QFP±0.025mm Cpk ≥1.0 (3σ)
Mounting Height	≦16mm (Other height can be customized)
Mounting Speed	98000 CPH(Under best condition)
Components	0201~12MM packaging material and IC material(Optional fixed camera for 0201~35*35MM),Other component size can be customized
Components Space	0.2mm
No. of Feeders Station	104 PCS
No. of nozzles	20 PCS
Power	220AC 50HZ
Power Consumption	1.5kw
Operating Environment	23 ±3
Transmission Speed	1000mm/sec
Transmission Direction	Single(left→ right or right→ left)
Transmission Mode	Online drive
Position Mode	Optical
Gas consumption	0.4-0.6mpa (4-6kgf/cm2)600N/min
Electrical control	Independent research and development by ETON
Motion control card module 1 set	Independent research and development by ETON
X,Y,Z Axis Drive way	High-end magnetic linear motor
Feeding way	Intelligent feeder with double motor
Production management MES system interface	Customized

Applications

ETON SMT MACHINE



Our advantage

ETON is the pioneer of SMT machine field in China which have more than 18 years experiences. And owned CCC, SIRA, CE certificates with 9 invention patents, 112 practical patents, 12 software copyrights of intellectual property technologies. Oversea market: The products exported to more than 30 countries and regions, including South Korea, India, Vietnam, Tunisia, Egypt, Turkey, Russia, Brazil etc.

Shipping and Delivery

As to the part of shipping and delivery, there are three ways for your reference, and different way is for different situations: Land transportation: suitable for inland countries and it is affordable;

Air freight: for urgent good, and it is the most expensive transportation way;

Shipping: It's suitable for heavy goods, and the convenience and lower cost of shipping which is easy for clients to accept the arrival time of the goods.



Shenzhen Eton Automation Equipment Co., Ltd.







HENGFENG INDUSTRIAL AREA,ZHOUSHI ROAD NO. 739,HEZHOU COMMUNITY,HANGCHENG STREET,BAOAN,SHENZHEN,CHINA